




Type TLW

**Designed for improved manpack communications
in paramilitary tactical situations**




The HF Lightweight is both compact and easy to carry, being constructed from ten lightweight tubular sections with flared ends that socket together in seconds.

The larger diameter lower four sections provide added stability.

The system features an internal shock cord system, which constrains the sections and facilitates fast deployment in the field. It makes use of the existing transceiver or ATU RF screw connector. The antenna is broken down easily into 300mm (11.8in) lengths. The overall height when erected is 3.0 metres (9.8ft). A flexible gooseneck is available as an option.

Connection to the radio may be via a screw connector at the radio ATU interface or via the optional gooseneck coupling.



Specifications

Colour	Standard is Black
Frequency Band	HF 2-30 MHz (with suitable radio/tuner)
Element Length	Extended: 3m (9.85ft) approx. {3.14m (10.3ft) with gooseneck}; Disassembled: 320mm (12.6in) approx.
Base Connection (Antenna)	Stainless steel threaded stud 3/8 in x 24 TPI or 8mm x 1mm (specify other threads to order)
Optional Gooseneck Coupling	Screw connection to radio (specify thread)
Gooseneck Length	200mm (7.9in) approx.
Colour and Finish	Drab olive green or black polyurethane paint (specify)
Polarisation	Vertical (typical)
Weight	Antenna: 320g (11.3 ozs); optional gooseneck 120g (7 ozs)

**Optional
Gooseneck
Coupling**

Specifications subject to change – Issued 01/09/13

Moonraker Australia Pty. Ltd. ABN 70 162 868 475
Tasmanian Technopark, Dowsing Point, Tasmania, Australia 7010

Website: www.moonraker.com.au Tel: 61 (0)3 6273 1533 Fax: 61 (0)3 6273 1749 Email: radiocom@moonraker.com.au

