

CEL-SM

FOR IMPROVED VEHICLE BASED COMMUNICATIONS. SUITABLE FOR MOBILE PHONE NETWORKS INCLUDING NEXTG, 2G, 3G, 4G, 4GX


CEL is a high gain, high strength vertically polarised collinear array antenna designed for use in the marine mobile and land environments.

The CEL-SM antenna system is ideal for fringe area operation being suitable for both inshore marine and land communications including remote building sites, temporary bases and vehicles.

The efficiency of both reception and transmission is improved over the mobile network, especially when operating in fringe areas where signal power is significantly reduced and the fading of signal strength causes communication difficulties. Signals are transmitted at the required field intensity using less power, thus significantly reducing drain on the mobile battery.

Antennas are fully marinised, with a fibreglass radome providing high strength protection for the radiating element. This together with a powder coated aluminium mounting tube ensures a high degree of strength and long operational life. It can be supplied for side mounting or with a strong multi-angled swing down mount. Six meters of low loss UHF co-axial cable is supplied to connect to the mobile phone.

Includes a stainless steel spring base and fastening bolt for vehicle mounting. Also available as a matched pair with the Moonraker CL3-SM UHF CB antenna.



SPECIFICATIONS ▼

	STANDARD	OPTIONAL
Colour	Black	White
Frequency Range	600MHz – 2.5GHz	
Polarisation	Vertical Omnidirectional	
Power	50 watts maximum	
VSWR	Less than 3:1 between 600 MHz – 2.5 GHz (typically 2.5 :1) Less than 2.5:1 between 700 MHz – 800 MHz Less than 2:1 between 800 MHz – 1.0 GHz (typically 1.5 :1)	
Gain	+5 dBi	
Impedance	50 ohms (nominal)	
Length	1.6m with standard mounting pole (alternate lengths on request) Minimum 500 mm with 1" or 12mm base mount options	
Wind Survival	Radome is designed to withstand up to 200 km/h	
Temperature	-50 to +55°C 100% humidity	
Connection	FME female crimp connector - other connectors to order 6m of RG58 extra low loss coaxial cable	
Mounting (see illustration)	Stainless Steel Spring base with Ø1/2" fastening bolt	
Weight	Unpacked: 1.7kg Packed: 3kg	
Warranty	12 months	



Mounting:

SWINGDOWN MOUNT

1. Place the base plate (of the mount) in the desired position and use it as a template.
2. Mark the position of the mounting holes.
3. Drill 4 x 6.4mm (1/4 in) diameter holes.
4. Bolt the mount/antenna in place

M12 BASE MOUNT ADAPTOR

1. Mark the mounting position on a horizontal surface or bracket that allows a minimum of 38mm diameter surface area.
2. Drill a 13mm (1/2 in) hole in the marked position.
3. Using a 12mm stainless steel or galvanised bolt fasten the antenna down firmly.
DO NOT OVERTIGHTEN AS THREAD MAY STRIP IN NYLON BASE.

SIDE MOUNTING

1. Use heavy duty clamps or strong hose clamps.
2. Space them 300mm apart.
3. Do not over tighten.
4. Do not drill stainless steel mounting tube.

Important Factors:

1. The top 80 cm of the antenna must be in free space, well away from other objects, antennas, etc. Mounting it as high as possible will assist performance. Vertical is best.
2. The base/mounting tube section of the antenna must not be drilled or damaged.
3. Supplied cable may be shortened. It may be lengthened but performance will be degraded due to signal/coaxial losses.
4. Due to internal arrangements the antenna will exhibit an open circuit if tested with an ohm meter or DC tester.
5. When using a swingdown mount allow sufficient cable to permit the antenna to swingdown without cable strain.

CBG Systems

9 Bender Drive, Derwent Park
Tasmania, AUSTRALIA 7009

T +61 3 6272 6105

F +61 3 6273 1716

E info@cbgsystems.com

www.cbgsystems.com

